FAST TRACKS	TEMPLATE		Printing Instructions:		Notes:	
Wye Scale HOn3 Outside Radius Inside Radius Produced Using NMRA RP's & Standards Mar 2008 V 2.00		 Select the Print option in the Adobe toolbar. Be sure that all page scaling, and fitting options are turned off. Setup your printer to use the highest possible quality settings. Select 8-1/2" X 11" (Letter) paper in landscape mode. Confirm that the template has been printed at the correct size by measuring the scale with a ruler or vernier caliper. If the template is printed on multiple pages, use the targets to align the pages and fasten them together. 		 The location of the rails is for reference only and should not be used for the placement of rail. We are always updating and refining our printable tie templates. Always be sure that you are using the most recent version. For a complete selection of up-to-date templates, visit us on the web at www.handlaidtrack.com. Shaded ties indicate the location of the PC Board ties. Gaps that are needed for DC and DCC compatibility are indicated with a blank area on the shaded ties and rails. 		
NOT BE LIABLE FOR ANY DAMAGES INCLUDIN	IG, BUT NOT LIMITED TO, DIR	ECT, INDIRECT, S		OTHER LOSSES ARISING OUT OF THE USE OF (R INABILITY TO USE THIS TEMPLATE. Of course, if errors are disco	& QUADICA DEVELOPMENTS INC, NOR ANY OF THEIR EMPLOYEES SHALL wered, we certainly do appreciate it if you bring them to our attention.
		Detaile	Specifications			→ 0.25" → 1.00" →
	Default Turnout Length 8.9" (226 mm)			L - 0.97" (24.5 mm)		
Minimum Turnout Length	5.5" (140 mm)		Tie Size (Scale)	W - 0.08" (2.1 mm)		
	9.46 (Decimal)			H - 0.06" (1.6 mm)		
Diverging Route Angle				L - 7' (2134 mm)		
	1:6 (Ratio)		Tie Size (Actual)	W - 7" (178 mm)		
Diverging Route Radius				H - 5" (127 mm)		
	22" (559 mm)		Secondary Frog Angle			
•	auge 0.42" (10.7 mm)			Substitution Radius 87"		
Track Spacing NA			These specifications are subject to change or correction.			
			mpleted turnout on their layout. Rail and PC I he positioning of the wood ties may not be exa			

