## FAST TRACKS TIE TEMPLATE TURNOUT Scale Outside Radius Inside Radius Froduced To NMRA Standards Dec 2008 V 2.01

## Printing Instructions:

- Select the Print option in the Adobe toolbar.
- Be sure that all page scaling, and fitting options are turned off.
   Setup your printer to use the highest possible quality settings.
- Select 8-1/2" X 11" (Letter) paper in landscape mode.
- Confirm that the template has been printed at the correct size by measuring the scale with a ruler or vernier caliper.
   If the template is printed on multiple pages, use the targets to align the pages and fasten them together.

## Notes:

- 1. The location of the rails is for reference only and should not be used for the placement of rail.
- 2. We are always updating and refining our printable tie templates. Always be sure that you are using the most recent version.
- For a complete selection of up-to-date templates, visit us on the web at www.handlaidtrack.com.
- 4. Shaded ties indicate the location of the PC Board ties.
- Gaps that are needed for DC and DCC compatibility are indicated with a blank area on the shaded ties.

USCLAIMER: While we have made every effort to ensure that this template is accurate, we cannot guarantee it to be 100% free from errors or inaccuracies. This template is provided "as is" without warranty of any kind, either expressed or implied. FAST TRACKS & QUADICA DEVELOPMENTS INC, NOR ANY OF THEIR EMPLOYEES SHAL
OT BE LIABLE FOR ANY DAMAGES INCLUDING, BUT NOT LIMITED TO, DIRECT, INDIRECT, SPECIAL INCIDENTAL OR CONSEQUENTIAL DAMAGES ON OTHER LOSSES ARISING OUT OF THE USE OF OR INABILITY TO USE THIS TEMPLATE OF course, if errors are discovered, we certainly do appreciate it if you bring them to our attention.

Purchase all of the tools & supplies that you need to build this trackwork at www.handlaidtrack.com or call us toll free at 1-888-252-3895







