FAST TRACKS TIE TEMPLATE Crossing Size Outside Radius Inside Radius Produced To NMRA Standards Mar 2006 V 2.00

Notes:

- The location of the rails is for reference only and should not be used for the placement of rail.
 We are always updating and refining our printable tie templates. Always be sure that you are using the most recent version.
- you are using the most recent version.

 3. For a complete selection of up-to-date templates, visit us on the web at www.handlaidtrack.com.
- 4. Shaded ties indicate the location of the PC Board ties.
- Gaps that are needed for DC and DCC compatibility are indicated with a blank area on the shaded ties.

JUSCLAMMERS While we have made every entor to ensure that this template is accurate, we cannot guiarantee it to be 100% there from errors or maccuracies. In its template is provided: as is without warranty of any kind, either expressed or implicate. HALLS & QUADLICA LEVELUPMENTS INC., NOT BET LIBERT ESPECTATION BUTTET TO STREET, TRIBBERT ESPECTATION BUTTET TO STREET, TRIBBERT ESPECTATION BUTTET TO STREET, AND REPORT AND ADMARGES NOT DETHELD STREET, AND REPORT AND ADMARGES NOT DETHELD STREET, AND REPORT ADMARGES NOT ADMA

Purchase all of the tools & supplies that you need to build this trackwork at www.handlaidtrack.com or call us toll free at 1-888-252-3895

align the pages and fasten them together.

- Select the Print option in the Adobe toolbar.

- Be sure that all page scaling, and fitting options are turned off.

- Setup your printer to use the highest possible quality settings.

- Confirm that the template has been printed at the correct size

- If the template is printed on multiple pages, use the targets to

- Select 8-1/2" X 11" (Letter) paper in landscape mode.

by measuring the scale with a ruler or vernier caliper.

Printing Instructions:





